

Milling Drilling Machine

Model: **PDM-30**

Features

- Spindle is equipped with four heavy-duty tapered roller bearings
- Table control hand wheels have large micrometer dials graduated in .001"
- Head swivels 360° and is easily raised and lowered
- Comes with 3" face cutter, 1/2" chuck with key and 3 1/2" angle vise



Model
 Drilling capacity
 Max. distance spindle nose to table
 Swing
 Spindle taper
 Spindle Stroke
 Diameter of Column
 Speeds
 Face mill capacity
 End mill capacity
 Max. table travel
 Working area of table
 Size of T-Slot on table
 Motor
 Voltage
 Pre-wired at
 Dimensions (LxWxH)
 Approx. shipping weight

PDM-30
 1 1/4"
 18 7/8"
 16 1/2"
 R8
 5"
 4 3/4"
 12 (150-2500) RPM
 3"
 3/4"
 17 1/2"
 8 1/4" x 28 3/4"
 5/8"
 22 amp. @ 110V, 11 amp. @ 220V
 110/220V, 1 phase, 60 Hz
 110V
 43" x 39" x 42"
 600 LBS

Accessories



Stand
SS-45



52 Pc. Clamping Kit
KCL-52



Swivel Base Milling Vise
KMV-4N/KMV-6N
KMV-8N



20 Pc. Titanium Coated End Mill
Set
KM-120